

# Section 7. Springs, shock absorbers, wheels

## Group 77 Wheels, tyres, hubs

### Wheels

|                         |          |       |
|-------------------------|----------|-------|
| Wheel rims              | Aluminum | Steel |
| Lateral runout.....max. | 0.8      | 1.0   |
| Radial runout.....max.  | 0.6      | 0.8   |

| Tyre pressures, cold tyres, kPa(psi) |                               |              |                        |              |
|--------------------------------------|-------------------------------|--------------|------------------------|--------------|
| Tyre size                            | 1 - 3 passengers<br>(comfort) |              | Full load<br>(economy) |              |
|                                      | Front                         | Rear         | Front                  | Rear         |
| <b>740</b>                           |                               |              |                        |              |
| 4-door                               | 190 (28)                      | 190 (28)     | 210 (30) 36*           | 260 (38) 36* |
| 5-door                               | 190 (28)                      | 210 (30)     | 210 (30)               | 280 (41) 36* |
| <b>940</b>                           |                               |              |                        |              |
| 4-door                               | 190 (28)                      | 190 (28)     | 210 (30) 36*           | 260 (38) 36* |
| 5-door                               | 190 (28)                      | 210 (30)     | 210 (30)               | 280 (41) 36* |
| <b>960</b>                           |                               |              |                        |              |
| 4-door                               | 200 (29) 28*                  | 190 (28)     | 210 (30) 36*           | 260 (38) 36* |
| 5-door                               | 190 (28)                      | 210 (30) 28* | 210 (30)               | 280 (41) 36* |
| Spare tyre<br>'Temporary spare'      | 350 (50) 40*                  | 350 (50) 40* | 350 (50) 40*           | 350 (50) 40* |

\* For certain markets (psi). Check with owners manual.

For sustained driving at high speed (above 160 km/h) tyre pressure in cold tyres should be raised by 30 kPa (4PSI).

### Tightening torques

|             |    |        |
|-------------|----|--------|
|             | Nm | ft. lb |
| Wheel ..... | 85 | 63     |