Section 7 Suspension, damping, wheels

Section 7 Suspension, damping, wheels

Group 77 Wheels, tyres, hubs

Wheel

	Wheel, aluminium rim	Wheel, steel rim
Dimensions	6.5Jx15x43	6Jx15x43
	6.5Jx16x43	6.5Jx15x43
	7Jx17x43	6.5Jx16x43
Lateral runout, maximum mm	0.4	0.8
Radial runout, maximum mm	0.4	0.7

Tightening torques

Wheel studs	Nm (ft. lb.)	110 (81)	Í.
wheel studs	 (it. ib.)	110 (01)	i.

All cars with AWD and cars with viscous coupling differentials have special instructions which must be followed

regarding differences in tyre wear.

The make and dimensions of the tyres must be the same on every wheel.

Otherwise the viscous coupling differential may be damaged.

Tyres

Tyre sizes	
185/65 R 15	FWD, recommended winter tyre size
195/60 R 15	FWD, standard size except for the Turbo (petrol engine)
195/65 R 15	AWD, recommended winter tyre size
205/55 R 15	FWD, 2.5 LT
205/65 R 15	XC AWD
205/50 R 16	FWD, standard size Turbo (petrol engine)
205/55 R 16	AWD, standard size. FWD, only USA/CAN, South Africa, Latin America
205/45 R 17	FWD, RF type required, LI88, not TDI
215/45 R 17	AWD, RF type required, LI91
T115/70 R 15	FWD, T-spare
T125/90 R 15	AWD, T-spare
T125/80 R 17	FWD, AWD, T-spare

Tyre pressure S70/petrol engines, not turbocharged:

Tyre pressure, cold tyres kPa							
Tyre sizes	Vehicle speed	1-3 p	eople	Full load			
	km/h	Front	Rear	Front	Rear		
185/65 R 15 M/S	0 - 160	220	200	230	250		
195/60 R 15 205/55 R 15 205/50 R 16	High-speed driving > 160	250	250	260	280		
"T-spare" T115/70 R 15	0 - 80	420	420	420	420		

Tyre pressure V70/petrol engines, not turbocharged:

Tyre pressure, cold tyres kPa							
Tyre sizes	Vehicle speed	ed 1-3 people Full load					
	km/h	Front	Rear	Front	Rear		
185/65 R 15 M/S	0 - 160	220	210	240	280		
195/60 R 15 205/55 R 15 205/50 R 16	High-speed driving > 160	250	250	260	310		
"T-spare" T115/70 R 15	0 - 80	420	420	420	420		

Tyre pressure S70/T5 and cars with engine B 5254 T

Tyre pressure, cold tyres kPa						
Tyre sizes	Vehicle speed	1-3 p	eople	Full load		
	km/h	Front	Rear	Front	Rear	
185/65 R 15 M/S	0 - 160	230	210	250	250	
205/55 R 15 205/50 R 16	High-speed driving > 160	280	260	290	290	
"T-spare" T115/70 R 15 T125/80 R 17	0 - 80	420	420	420	420	

Group 77 Wheels, tyres, hubs

Tyre pressure V70/T5 and cars with engine B 5254 T

Tyre pressure, cold tyres kPa						
Tyre sizes	Vehicle speed	1-3 p	eople	Full load		
	km/h	Front	Rear	Front	Rear	
185/65 R 15	0 - 160	230	220	250	280	
M+S 205/55 R 15 205/50 R 16	High-speed driving > 160	280	270	290	320	
"T-spare" T115/70 R 15 T125/80 R 17	0 - 80	420	420	420	420	

Tyre pressure S70, 17" tyres

Tyre pressure, cold tyres, 17" kPa							
Tyre sizes	Vehicle speed	1-3 people		Full load			
	km/h	Front	Rear	Front	Rear		
205/45 ZR 17 88 W 205/50 R 16 M+S	0 - 160	230	210	250	250		
	High-speed driving > 160	310	260	330	290		
"T-spare" T115/70 R 15 T125/80 R 17	0 - 80	420	420	420	420		

Tyre pressure V70, 17" tyres

Tyre pressure, cold tyres, 17" kPa							
Tyre sizes	Vehicle speed	1-3 p	eople	Full load			
	km/h	Front	Rear	Front	Rear		
205/45 ZR 17 88 W 205/50 R 16 M+S	0 - 160	230	220	250	280		
	High-speed driving > 160	310	270	330	320		
"T-spare" T115/70 R 15 T125/80 R17	0 - 80	420	420	420	420		

<u>S/V70</u> Group 77 Wheels, tyres, hubs

Tyre pressure S70 Diesel

Tyre pressure, cold tyres kPa							
Tyre sizes	Vehicle speed	1-3 p	1-3 people		load		
,	km/h	Front	Rear	Front	Rear		
185/65 R 15	0 - 160	250	210	280	260		
M+S 195/60 R 15	High-speed driving > 160	270	250	290	280		
"T-spare" T115/70 R 15	0 - 80	420	420	420	420		

Tyre pressure V70 Diesel

Tyre pressure, cold tyres kPa							
Tyre sizes	Vehicle speed	1-3 people		Full load			
	km/h	Front	Rear	Front	Rear		
185/65 R 15	0 - 160	250	220	280	280		
M+S 195/60 R 15	High-speed driving > 160	270	260	290	300		
"T-spare" T115/70 R 15	0 - 80	420	420	420	420		

Tyre pressure V70 AWD and V70 XC AWD:

Tyre pressure, cold tyres kPa						
Tyre sizes	Vehicle speed		1-3 people		load	
	km/h	Front	Rear	Front	Rear	
195/65 R 15	0 - 160	220	230	250	280	
M+S 205/55 R 16	High-speed driving > 160	260	270	280	320	
	0 - 160	250	250	260	280	
215/45 R 17	High-speed driving > 160	300	300	310	330	
"T-spare" (T125/90 R 15) T125/80 R 17	0 - 80	420	420	420	420	